

# **GIRDER TROLLEY WITH CLAMP**

# Capacities: 1 tonne to 5 tonnes

- Robust all-steel construction
- Durable baked enamel paint protection
- Super-quick adjustment to any girder width in range
- Spare parts always available


Product Code		OGCT01	OGCT02	OGCT03	OGCT05	
Working Load Limit kg		1000	2000	3000	5000	
Test load	kN	12.25	24.5	36.8	61.3	
Min. radius	mm	1.1	1.3	1.5	1.7	
	Α	260	260	330	380	
Clearance	В	340	340	360	480	
Dimensions	С	Ø <b>20</b>	Ø20	ø24	ø24	
mm	D	10	12	14	19	
	Н	171-232	237-285	160-200	225-280	
Beam width Net Weight	mm kg	63-203 11	76-203 13	85-210 26	100-305 46	
Two two igni	ĸg	• • •				


#### **COMPLIES WITH AS/NZS1418.2**



### Capacities: 1 tonne to 10 tonnes

- Robust all-steel construction
- Durable baked enamel paint protection
- Super-quick adjustment to any girder width in range
- Spare parts always available





	Working Adjustable		Α	В		С	D	Е	F		G	Н
Product Code	Load Limit	Beam Width	max.	min.	max.				max.	min.	min.	
	kg	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
OGC1	1000	75-230	278	182	380	64	4	217	150	90	26	19
OGC2	2000	75-230	278	182	380	74	6	217	150	90	26	21
OGC3	3000	80-320	356	220	500	100	8	277	220	145	50	23
OGC5	5000	90-320	356	220	500	112	10	277	220	145	47	29
OGC10	10000	90-320	356	250	520	120	12	285	230	160	52	39

### **COMPLIES WITH AS4991**